

<b>MI-setral-7 NR (Spray)</b>	Nr. 0504
MoS <sub>2</sub> assembly paste with low coefficient of friction.	Packaging: 400ml aerosol

### Application

Special assembly paste for micro-finished surfaces.

### Characteristics

- Reduces wear and tear
- Highest load carrying ability
- Low friction coefficient
- Outstanding emergency running characteristics
- Avoids stick-slip
- No metal welding during shaping

### Method of use

- Best before in original sealed packaging and dry and cool storage (no direct sun light) ca. 2 years.

### Technical data

Colour	dark grey-black		DIN ISO 2049
Thickener	organic		
Density 15°C	1,42	g/cm <sup>3</sup>	DIN ISO 51757
Temperature range	- 30 - + 450	°C	
Temperature range under vacuum	- 30 - + 630	°C	

Setral Chemie GmbH  
 Salzsteinstrasse 4  
 D-82402 Seeshaupt  
 Telefon: +49 (0) 88 01 97 10  
 Telefax: +49 (0) 88 01 97 30  
 Email: info@setral.net

Sétral S.á.r.l.  
 13, rue Tannmuhle  
 F-67310 Romanswiller  
 Téléphone: +33 (0) 3 88 59 11 59  
 Télécopie: +33 (0) 3 88 59 11 57  
 Email: france@setral.net

The information in this bulletin is, to our knowledge, true and accurate, but all recommendations are without guarantee, since the conditions of use are beyond our control. Setral disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.